LEGISLATIVE HISTORY CHECKLIST

Compiled by the NJ State Law Library

LAWS of 1999

CHAPTER: 29

NJSA: 39:3-84

(Tractors -- wheelbase length)

BILL NO:A1284

SPONSOR(S):DeCroce and Charles

DATE INTRODUCED: Pre-filed

COMMITTEE:

ASSEMBLY: Transportation SENATE: Transportation

AMENDED DURING PASSAGE: No

DATE OF PASSAGE:

ASSEMBLY: May 18, 1998 **SENATE:** January 12, 1999

DATE OF APPROVAL:February 26, 1999

THE FOLLOWING ARE ATTACHED IF AVAILABLE:

FINAL TEXT OF BILL: Original

(Amendments during passage denoted by superscript numbers)

A1284

SPONSORS STATEMENT: Yes (Begins on page 10 of original bill)

COMMITTEE STATEMENT:

ASSEMBLY: Yes SENATE: Yes

FLOOR AMENDMENT STATEMENTS: No

LEGISLATIVE FISCAL ESTIMATE: No

VETO MESSAGE: No

GOVERNOR'S PRESS RELEASE ON SIGNING: Yes

THE FOLLOWING WERE PRINTED:

To check for circulating copies contact New Jersey State Government Publications at the State Library (609) 278-2640 ext. 102 or refdesk@njstatelib.org

REPORTS: No

HEARINGS: No

NEWSPAPER ARTICLES: No

P.L. 1999, CHAPTER 29, approved February 26, 1999 Assembly, No. 1284

AN ACT concerning truck dimensions and amending R.S.39:3-84. 1

2 3

BE IT ENACTED by the Senate and General Assembly of the State of New Jersey:

4 5 6

14

15

16

17

18

19

20

21

22

23

24 25

26 27

28

29

30

31

32

33

34 35

36 37

38 39

40

1. R.S.39:3-84 is amended to read as follows:

7 39:3-84. a. The following constitute the maximum dimensional limits for width, height and length for any vehicle or combination of 8 9 vehicles, including load or contents or any part or portion thereof, 10 found or operated on any public road, street or highway or any public 11 or quasi-public property in this State. Violations shall be enforced pursuant to subsection i. of section 5 of P.L.1950, c.142 12 (C.39:3-84.3). 13

The dimensional limitations set forth in this subsection are exclusive of safety and energy conservation devices necessary for safe and efficient operation of a vehicle or combination of vehicles, including load or contents, except that no device excluded herein shall have by its design or use the capability to carry, transport or otherwise be utilized for cargo.

Any rules and regulations authorized to be promulgated pursuant to this subsection shall be consistent with any rules and regulations promulgated by the Secretary of Transportation of the United States of America, and shall be in accordance with the provisions of the "Administrative Procedure Act," P.L.1968, c.410 (C.52:14B-1 et seq.). In addition to the other requirements of this subsection and notwithstanding any other provision of this Title, no vehicle or combination of vehicles, including load or contents or any part or portion thereof, except as otherwise provided by this subsection shall be operated in this State, unless by special permit authorized by subsection d. of this section with a dimension, the allowance of which would disqualify the State of New Jersey or any department, agency or governmental subdivision thereof for the purpose of receiving federal highway funds.

As used herein and pursuant to R.S.39:1-1, the term "vehicle" includes, but is not limited to, commercial motor vehicles, trucks, truck tractors, tractors, road tractors, recreation vehicles, or omnibuses. As used herein and pursuant to R.S.39:1-1, the term "combination of vehicles" includes, but is not limited to, vehicles as heretofore designated, when those vehicles are the drawing or power unit of a combination of vehicles and motor-drawn vehicles, such as, but not limited to, trailers, semi-trailers, or other vehicles. As used

41

EXPLANATION - Matter enclosed in bold-faced brackets [thus] in the above bill is not enacted and intended to be omitted in the law.

- 1 herein, the term "recycling vehicle" means a commercial motor vehicle
- 2 used for the collection or transportation of recyclable material; or any
- 3 truck, trailer or other vehicle approved by the New Jersey Office of
- 4 Recycling for use by persons engaging in the business of recycling or
- 5 otherwise providing recycling services in this State; and "recyclable
- 6 material" means those materials which would otherwise become solid
- 7 waste, and which may be collected, separated or processed and
- 8 returned to the economic mainstream in the form of raw materials or
- 9 products.

- (1) The maximum outside width of any vehicle or combination of vehicles, including load or contents of any part or portion thereof, except as otherwise provided by this subsection, shall be no more than 102 inches; except that the Commissioner of Transportation, after consultation with the Director of the Division of Motor Vehicles and the Superintendent of State Police, may promulgate rules and regulations for those public roads, streets or highways or public or quasi-public property in this State, where it is determined that the interests of public safety and welfare require the maximum outside width be no more than 96 inches.
- (2) The maximum height of any vehicle or combination of vehicles, including load or contents of any part or portion thereof, except as otherwise provided by this subsection, shall not exceed 13 feet, 6 inches.
- (3) The maximum overall length of any vehicle, as set forth in this subsection, including load or contents or any part or portion thereof, except as otherwise provided by this subsection, shall not exceed 40 feet, except that the overall length of a vehicle, including load or contents or any part or portion thereof, otherwise subject to the provisions of this paragraph shall not exceed 50 feet when transporting poles, pilings, structural units or other articles which cannot be dismembered, dismantled or divided. When a vehicle, subject to this paragraph, is the drawing or power unit of a combination of vehicles, as set forth in this subsection, the overall length of the combination of vehicles, including load or contents or any part or portion thereof, shall not exceed 62 feet. The provisions of this paragraph shall not apply to omnibuses or to vehicles which are not designed, built or otherwise capable of carrying cargo or loads.
- (4) The maximum overall length of a motor-drawn vehicle, as set forth in this subsection, including load or contents or any part or portion thereof, except as otherwise provided by this subsection, shall not exceed 53 feet when operated as part of a combination of vehicles consisting of one motor-drawn vehicle and a drawing or power unit vehicle not designed, built or otherwise capable of carrying cargo or loads, except that a motor-drawn vehicle, the overall length of which is greater than 48 feet and not more than 53 feet, shall be constructed so that the distance between the kingpin of the motor-drawn vehicle

1 and the centerline of its rear axle or rear axle group does not exceed 2 41 feet; the motor-drawn vehicle shall be equipped with a rear-end 3 protection device of substantial construction consisting of a 4 continuous lateral beam extending to within four inches of the lateral 5 extremities of the motor-drawn vehicle and located not more than 22 inches from the surface as measured with the vehicle empty and on a 6 7 level surface; the kingpin of the trailer shall not be set back further 8 than 3.5 feet from the front of the semitrailer; the rear overhang, 9 measured from the center of the rear tandem axles to the rear of the 10 semitrailer shall not exceed 35% of the semitrailer's wheelbase; [the 11 tractor wheelbase shall not exceed 20 feet between the center of the 12 front axle and the center of the rear single axle or tandem axles; I the width of the semitrailer and the distance between the outside edges of 13 14 the trailer tires shall be 102 inches; and the vehicle shall be equipped 15 with such reflectorization, including but not limited to side-marker reflectorization strips located between the rear axle and the rear of the 16 17 motor-drawn vehicle, as shall be prescribed by the Division of Motor Vehicles, and as is consistent with any applicable federal standards 18 concerning reflectorization. The overall length of a motor-drawn 19 20 vehicle otherwise subject to the provisions of this paragraph shall not 21 exceed 63 feet when transporting poles, pilings, structural units or 22 other articles that cannot be dismembered, dismantled or divided. The 23 provisions of this paragraph shall not apply to any vehicle or 24 combination of vehicles designed, built and utilized solely to transport other motor vehicles. The Commissioner of Transportation, after 25 26 consultation with the Director of the Division of Motor Vehicles and the Superintendent of State Police, shall promulgate rules and 27 28 regulations specifying those portions or parts of the National System 29 of Interstate and Defense Highways, Federal-aid Primary System 30 Highways and public roads, streets, highways, toll roads, freeways or 31 parkways in this State where the combination of vehicles as described 32 in this paragraph may lawfully operate. The commissioner shall 33 promulgate rules and regulations within 120 days after the effective 34 date of this amendatory act to identify a network of roads with 35 reasonable access for motor-drawn vehicles greater than 48 feet in length but not more than 53 feet in length. The commissioner shall, in 36 37 establishing this network, consider all portions of the network for 48 38 foot long and 102 inch wide motor-drawn vehicles and specify those 39 routes or portions thereof where motor-drawn vehicles greater than 48 40 feet in length but not more than 53 feet in length shall be excluded 41 from lawful operation for reasons of safety. 42

(5) No combination of vehicles, including load or contents, consisting of more than two motor-drawn vehicles, as set forth in this subsection, and any other vehicle, shall be found or operated on any public road, street or highway or any public or quasi-public property in this State.

43

44

45

- 1 (6) The maximum overall length of a motor-drawn vehicle, as set 2 forth in this section, including load or contents or any part or portion 3 thereof, except as otherwise provided by this subsection, when 4 operated as part of a combination of vehicles consisting of two motor-drawn vehicles and a drawing or power unit vehicle which is 5 6 not designed, built or otherwise capable of carrying cargo or loads, 7 shall not exceed 28 feet for each motor-drawn vehicle in the 8 combination of vehicles. The provision of this paragraph shall not 9 apply to any vehicle or combination of vehicles designed, built and 10 utilized solely to transport other motor vehicles. The Commissioner of Transportation, after consultation with the Director of the Division of 11 12 Motor Vehicles and the Superintendent of State Police, shall 13 promulgate rules and regulations specifying those portions or parts of 14 the National System of Interstate and Defense Highways, Federal-aid 15 Primary System Highways and public roads, streets, highways, toll 16 roads, freeways or parkways in this State where combinations of 17 vehicles as described in this paragraph may lawfully operate. 18
 - (7) The maximum length and outside width of an omnibus found or operated in this State shall be established by rules and regulations promulgated by the Commissioner of Transportation, consultation with the Director of the Division of Motor Vehicles and the Superintendent of State Police. Unless otherwise specified in the aforesaid rules and regulations, the maximum outside width shall be 102 inches; any other dimension established for width in the aforesaid rules and regulations shall be based upon a determination that operation of an omnibus with a width of less than 102 inches, but no less than 96 inches is required in the interest of public safety on those public roads, streets, highways, toll roads, freeways, parkways or the National System of Interstate and Defense Highways in this State specified in the aforesaid rules and regulations, or that operation of an omnibus with a width greater than 102 inches is not unsafe on those public roads, streets, highways, toll roads, freeways, parkways or the National System of Interstate and Defense Highways in this State specified in the aforesaid rules and regulations.

20

21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

37

38

39

40

41

42

43 44

45

- (8) The maximum width and length of farm tractors and traction equipment and farm machinery and implements shall be established by rules and regulations promulgated by the Director of the Division of Motor Vehicles. The operation of the aforesaid vehicles shall be subject to the provisions of R.S.39:3-24 and they shall not be operated on any highway which is part of the National System of Interstate and Defense Highways or on any highway which has been designated a freeway or parkway as provided by law.
- (9) The maximum outside width of the cargo or load of a vehicle or combination of vehicles, including farm trucks, loaded with hay or straw shall not exceed 105 1/2 inches, but the maximum outside width of the vehicle or combination of vehicles, including farm trucks, shall

- otherwise comply with the provisions of paragraph (1) of this subsection. The Commissioner of Transportation, after consultation with the Director of the Division of Motor Vehicles and the Superintendent of State Police, may promulgate rules and regulations establishing a maximum outside width of 102 inches for the aforesaid cargo or load when operating on those highways where a greater width is prohibited by operation of law.
 - (10) Notwithstanding the provisions of paragraphs (4) and (6) of this subsection pertaining to length, the Director of the Division of Motor Vehicles may adopt rules and regulations specifying maximum length dimensions for any vehicle or combination of vehicles designed, built and utilized solely to transport other motor vehicles.

- (11) The provisions of this subsection pertaining to length shall not apply to a vehicle or combination of vehicles or special mobile equipment operated by a public utility, as defined in R.S.48:2-13, when that vehicle or combination of vehicles or special mobile equipment is used by the public utility in the construction, reconstruction, repair or maintenance of its property or facilities.
- (12) The provisions of this subsection pertaining to width shall not apply to a recycling vehicle when that vehicle is used for the collection of recyclable material on a street or highway other than a highway which is designated part of the National System of Interstate and Defense Highways in this State or as a freeway or parkway as provided by law. The maximum outside width of any recycling vehicle so used, including load or contents of any part or portion thereof, shall be no more than 96 inches, except that the width may be up to 105 inches whenever that vehicle is operating at 15 miles per hour or less, and access steps are deployed and recyclable materials are actually being collected.
- b. No vehicle or combination of vehicles, including load or contents, found or operated on any public road, street or highway or any public or quasi-public property in this State shall exceed the weight limitations set forth in this Title. Violations shall be enforced pursuant to subsection j. of section 5 of P.L.1950, c.142 (C.39:3-84.3).

Where enforcement of a weight limit provision of this Title requires a measurement of length between axle centers, the distance between axle centers shall be measured to the nearest whole foot or whole inch, whichever is applicable, and when the measurement includes a fractional part of a foot equaling six inches or more or a fractional part of an inch equaling one-half inch or more, the next larger whole foot or whole inch, whichever is applicable, shall be utilized. The term "tandem axle" as used in this act is defined as a combination of consecutive axles, consisting of only two axles, where the distance between axle centers is 40 inches or more but no more than 96 inches. In addition to the other requirements of this section and notwithstanding any other provision of this Title, no vehicle or combination of vehicles, including load or contents, shall be operated in this State, unless by special permit authorized by this Title, with a gross weight, single or multiple axle weight, or gross weight of two or more consecutive axles, the allowance of which would disqualify the State of New Jersey or any department, agency or governmental subdivision thereof for the purpose of receiving federal highway funds.

(1) The gross weight imposed on the highway or other surface by the wheels of any one axle of a vehicle or combination of vehicles, including load or contents, shall not exceed 22,400 pounds.

For the purpose of this Title the combined gross weight imposed on the highway or other surface by all the wheels of any one axle of a vehicle or combination of vehicles, including load or contents, shall be deemed to mean the total gross weight of all wheels whose axle centers are spaced less than 40 inches apart.

- (2) The gross weight imposed on the highway or other surface by all the wheels of all consecutive axles of a vehicle or combination of vehicles, including load or contents, shall not exceed 34,000 pounds where the distance between consecutive axle centers is 40 inches or more, but no more than 96 inches apart.
- (3) The combined gross weight imposed on the highway or other surface by all the wheels of consecutive axles of a vehicle or combination of vehicles, including load or contents, shall not exceed 22,400 pounds for each single axle where the distance between consecutive axle centers is more than 96 inches; except that on any highway in this State which is part of, or designated as part of, the National Interstate System, as provided at 23 U.S.C.103(e), this single axle limitation shall not apply and in those instances the provisions of this Title as set forth at R.S.39:3-84b.(5) shall apply.
- (4) The maximum total gross weight imposed on the highway or other surface by a vehicle or combination of vehicles, including load or contents, shall not exceed 80,000 pounds.
- (5) On any highway in this State which is part of, or designated as part of, the National Interstate System, as provided at 23 U.S.C. 103(e), the total gross weight, in pounds, imposed on the highway or other surface by any group of two or more consecutive axles of a vehicle or combination of vehicles, including load or contents, shall not exceed that listed in the following Table of Maximum Gross Weights, for the respective distance, in feet, between the axle centers of the first and last axles of the group of two or more consecutive axles under consideration; except that in addition to the weights specified in that Table, two consecutive sets of tandem axles may carry a gross weight of 34,000 pounds each if the overall distance between the first and last axles of the consecutive sets of tandem axles is 36 feet or more. The gross weight of each set of tandem axles shall not exceed 34,000 pounds and the combined gross weight of the two

```
1
    consecutive sets of tandem axles shall not exceed 68,000 pounds.
 2
       In all cases the combined gross weight for a vehicle or combination
 3
    of vehicles, including load or contents, or the maximum gross weight
 4
    for any axle or combination of axles of the vehicle or combination of
 5
    vehicles, including load or contents, shall not exceed that which is
 6
    permitted pursuant to this paragraph or R.S.39:3-84b.(2);
 7
    R.S.39:3-84b.(3); or R.S.39:3-84b.(4) of this act, whichever is the
 8
    lesser allowable gross weight.
 9
10
    TABLE OF MAXIMUM GROSS WEIGHTS
11
       Distance in feet
12
       between axle
13
       centers of first
14
       and last axles
15
       of any group
16
       of two or more
       consecutive axles
17
18
                               5
                                            7
19
           axles
                 axles
                       axles axles
                                    axles axles
           22400 22400 22400 22400 22400 22400
20
    3
21
    4
           34000 34000 34000 34000 34000 34000
    5
           34000 34000 34000 34000 34000 34000
22
23
           34000 34000 34000 34000 34000 34000
    6
    7
           34000 34000 34000 34000 34000 34000
24
25
    8
           34000 34000 34000 34000 34000 34000
           39000 42500 42500 42500 42500 42500
26
    9
           40000 43500 43500 43500 43500 43500
27
     10
           41000 44000 44000 44000 44000 44000
28
     11
           42000 45000 50000 50000 50000 50000
29
     12
30
     13
           43000 45500 50500 50500 50500 50500
31
           44000 46500 51500 51500 51500 51500
     14
32
           44800 47000 52000 52000 52000 52000
     15
           44800 48000 52500 58000 58000 58000
33
     16
           44800 48500 53500 58500 58500 58500
34
     17
           44800 49500 54000 59000 59000 59000
35
     18
36
     19
           44800 50000 54500 60000 60000 60000
           44800 51000 55500 60500 66000 66000
37
    20
           44800 51500 56000 61000 66500 66500
38
    21
           44800 52500 56500 61500 67000 67000
39
    22
           44800 53000 57500 62500 68000 68000
40
    23
41
    24
           44800 54000 58000 63000 68500 74000
42
    25
           44800 54500 58500 63500 69000 74500
           44800 55500 59500 64000 69500 75000
43
    26
44
    27
           44800 56000 60000 65000 70000 75500
           44800 57000 60500 65500 71000 76500
45
    28
           44800 57500 61500 66000 71500 77000
46
    29
```

```
44800 58500 62000 66500 72000 77500
 1
    30
 2
    31
           44800 59000 62500 67500 72500 78000
 3
    32
           44800 60000 63500 68000 73000 78500
 4
    33
           44800 60500 64000 68500 74000 79000
 5
           44800 61500 64500 69000 74500 80000
    35
           44800 62000 65500 70000 75000 80000
 6
 7
           44800 63000 66000 70500 75500 80000
    36
           44800 63500 66500 71000 76000 80000
 8
    37
 9
    38
           44800 64500 67500 71500 77000 80000
10
    39
           44800 65000 68000 72500 77500 80000
    40
           44800 66000 68500 73000 78000 80000
11
12
    41
           44800 66500 69500 73500 78500 80000
          44800 67200 70000 74000 79000 80000
13
    42
           44800 67200 70500 75000 80000 80000
14
    43
    44
           44800 67200 71500 75500 80000 80000
15
           44800 67200 72000 76000 80000 80000
    45
16
           44800 67200 72500 76500 80000 80000
17
    46
    47
          44800 67200 73500 77500 80000 80000
18
           44800 67200 74000 78000 80000 80000
19
    48
           44800 67200 74500 78500 80000 80000
20
    49
21
    50
           44800 67200 75500 79000 80000 80000
22
    51
           44800 67200 76000 80000 80000 80000
23
           44800 67200 76500 80000 80000 80000
           44800 67200 77500 80000 80000 80000
24
    53
           44800 67200 78000 80000 80000 80000
25
    54
           44800 67200 78500 80000 80000 80000
26
    55
27
    56
           44800 67200 79500 80000 80000 80000
28
    57
           44800 67200 80000 80000 80000 80000
29
    58
           44800 67200 80000 80000 80000 80000
30
           44800 67200 80000 80000 80000 80000
    59
           44800 67200 80000 80000 80000 80000
31
    60
           44800 67200 80000 80000 80000 80000
32
    61
           44800 67200 80000 80000 80000 80000
33
    62
34
    63
           44800 67200 80000 80000 80000 80000
           44800 67200 80000 80000 80000 80000
35
    64
           44800 67200 80000 80000 80000 80000
36
    65
           44800 67200 80000 80000 80000 80000
37
    66
           44800 67200 80000 80000 80000 80000
38
    67
           44800 67200 80000 80000 80000 80000
39
           44800 67200 80000 80000 80000 80000
40
    69
41
           44800 67200 80000 80000 80000 80000
42
       c. The dimensional and weight restrictions set forth herein shall not
43
```

apply to a combination of vehicles which includes a disabled vehicle or a combination of vehicles being removed from a highway in this State, provided that such oversize or overweight vehicle combination may not travel on the public highways more than five miles from the point where such disablement occurred. If the disablement occurred on a limited access highway, the distance to the nearest exit of such highway shall be added to the five-mile limitation.

- d. The Director of the Division of Motor Vehicles may promulgate rules and regulations, including the establishment of fees, for the issuance, at his discretion and if good cause appears, of a special written permit authorizing the applicant:
- (1) To operate or move a vehicle or combination of vehicles or special mobile equipment, transporting one piece loads that cannot be dismembered, dismantled or divided in order to comply with the weight limitations set forth in this act. The special written permit issued by the director shall be in the possession of the driver or operator of the vehicle or combination of vehicles or special mobile equipment for which said permit was issued; and
- (2) To operate or move a vehicle or combination of vehicles or specialized mobile equipment, transporting a load or cargo that cannot be dismembered, dismantled or divided in order to comply with the dimensional limitations set forth in this act. The special written permit shall be in the possession of the driver or operator of the vehicle or combination of vehicles or special mobile equipment for which the permit was issued; and
- (3) Under emergency conditions, to operate or move a type of vehicle or combination of vehicles or special mobile equipment of a size or weight, including load or contents, which exceeds the maximum size or weight limitations specified in this act.

26 (cf: P.L.1995, c.397, s.3)

2. This act shall take effect immediately.

Removes requirement that tractor wheelbase of certain motor-drawn vehicles not exceed 20 feet between center of front axle and center of rear single axle or tandem axles.

ASSEMBLY, No. 1284

STATE OF NEW JERSEY

208th LEGISLATURE

PRE-FILED FOR INTRODUCTION IN THE 1998 SESSION

Sponsored by:

Assemblyman ALEX DECROCE District 26 (Essex, Morris and Passaic) Assemblyman JOSEPH CHARLES, JR. District 31 (Hudson)

SYNOPSIS

Removes requirement that tractor wheelbase of certain motor-drawn vehicles not exceed 20 feet between center of front axle and center of rear single axle or tandem axles.

CURRENT VERSION OF TEXT

As reported by the Assembly Transportation Committee with technical review.



1 AN ACT concerning truck dimensions and amending R.S.39:3-84.

BE IT ENACTED by the Senate and General Assembly of the State of New Jersey:

1. R.S.39:3-84 is amended to read as follows:

39:3-84. a. The following constitute the maximum dimensional limits for width, height and length for any vehicle or combination of vehicles, including load or contents or any part or portion thereof, found or operated on any public road, street or highway or any public or quasi-public property in this State. Violations shall be enforced pursuant to subsection i. of section 5 of P.L.1950, c.142 (C.39:3-84.3).

The dimensional limitations set forth in this subsection are exclusive of safety and energy conservation devices necessary for safe and efficient operation of a vehicle or combination of vehicles, including load or contents, except that no device excluded herein shall have by its design or use the capability to carry, transport or otherwise be utilized for cargo.

Any rules and regulations authorized to be promulgated pursuant to this subsection shall be consistent with any rules and regulations promulgated by the Secretary of Transportation of the United States of America, and shall be in accordance with the provisions of the "Administrative Procedure Act," P.L.1968, c.410 (C.52:14B-1 et seq.). In addition to the other requirements of this subsection and notwithstanding any other provision of this Title, no vehicle or combination of vehicles, including load or contents or any part or portion thereof, except as otherwise provided by this subsection shall be operated in this State, unless by special permit authorized by subsection d. of this section with a dimension, the allowance of which would disqualify the State of New Jersey or any department, agency or governmental subdivision thereof for the purpose of receiving federal highway funds.

As used herein and pursuant to R.S.39:1-1, the term "vehicle" includes, but is not limited to, commercial motor vehicles, trucks, truck tractors, tractors, road tractors, recreation vehicles, or omnibuses. As used herein and pursuant to R.S.39:1-1, the term "combination of vehicles" includes, but is not limited to, vehicles as heretofore designated, when those vehicles are the drawing or power unit of a combination of vehicles and motor-drawn vehicles, such as, but not limited to, trailers, semi-trailers, or other vehicles. As used herein, the term "recycling vehicle" means a commercial motor vehicle used for the collection or transportation of recyclable material; or any

EXPLANATION - Matter enclosed in bold-faced brackets [thus] in the above bill is not enacted and intended to be omitted in the law.

- 1 truck, trailer or other vehicle approved by the New Jersey Office of
- 2 Recycling for use by persons engaging in the business of recycling or
- 3 otherwise providing recycling services in this State; and "recyclable
- 4 material" means those materials which would otherwise become solid
- 5 waste, and which may be collected, separated or processed and
- 6 returned to the economic mainstream in the form of raw materials or
- 7 products.

- (1) The maximum outside width of any vehicle or combination of vehicles, including load or contents of any part or portion thereof, except as otherwise provided by this subsection, shall be no more than 102 inches; except that the Commissioner of Transportation, after consultation with the Director of the Division of Motor Vehicles and the Superintendent of State Police, may promulgate rules and regulations for those public roads, streets or highways or public or quasi-public property in this State, where it is determined that the interests of public safety and welfare require the maximum outside
 - (2) The maximum height of any vehicle or combination of vehicles, including load or contents of any part or portion thereof, except as otherwise provided by this subsection, shall not exceed 13 feet, 6 inches

width be no more than 96 inches.

- (3) The maximum overall length of any vehicle, as set forth in this subsection, including load or contents or any part or portion thereof, except as otherwise provided by this subsection, shall not exceed 40 feet, except that the overall length of a vehicle, including load or contents or any part or portion thereof, otherwise subject to the provisions of this paragraph shall not exceed 50 feet when transporting poles, pilings, structural units or other articles which cannot be dismembered, dismantled or divided. When a vehicle, subject to this paragraph, is the drawing or power unit of a combination of vehicles, as set forth in this subsection, the overall length of the combination of vehicles, including load or contents or any part or portion thereof, shall not exceed 62 feet. The provisions of this paragraph shall not apply to omnibuses or to vehicles which are not designed, built or otherwise capable of carrying cargo or loads.
- (4) The maximum overall length of a motor-drawn vehicle, as set forth in this subsection, including load or contents or any part or portion thereof, except as otherwise provided by this subsection, shall not exceed 53 feet when operated as part of a combination of vehicles consisting of one motor-drawn vehicle and a drawing or power unit vehicle not designed, built or otherwise capable of carrying cargo or loads, except that a motor-drawn vehicle, the overall length of which is greater than 48 feet and not more than 53 feet, shall be constructed so that the distance between the kingpin of the motor-drawn vehicle and the centerline of its rear axle or rear axle group does not exceed 41 feet; the motor-drawn vehicle shall be equipped with a rear-end

protection device of substantial construction consisting of a 1 2 continuous lateral beam extending to within four inches of the lateral 3 extremities of the motor-drawn vehicle and located not more than 22 4 inches from the surface as measured with the vehicle empty and on a level surface; the kingpin of the trailer shall not be set back further 5 6 than 3.5 feet from the front of the semitrailer; the rear overhang, measured from the center of the rear tandem axles to the rear of the 7 8 semitrailer shall not exceed 35% of the semitrailer's wheelbase; [the 9 tractor wheelbase shall not exceed 20 feet between the center of the 10 front axle and the center of the rear single axle or tandem axles; I the width of the semitrailer and the distance between the outside edges of 11 12 the trailer tires shall be 102 inches; and the vehicle shall be equipped 13 with such reflectorization, including but not limited to side-marker 14 reflectorization strips located between the rear axle and the rear of the motor-drawn vehicle, as shall be prescribed by the Division of Motor 15 16 Vehicles, and as is consistent with any applicable federal standards concerning reflectorization. The overall length of a motor-drawn 17 18 vehicle otherwise subject to the provisions of this paragraph shall not 19 exceed 63 feet when transporting poles, pilings, structural units or other articles that cannot be dismembered, dismantled or divided. The 20 21 provisions of this paragraph shall not apply to any vehicle or 22 combination of vehicles designed, built and utilized solely to transport 23 other motor vehicles. The Commissioner of Transportation, after 24 consultation with the Director of the Division of Motor Vehicles and the Superintendent of State Police, shall promulgate rules and 25 26 regulations specifying those portions or parts of the National System 27 of Interstate and Defense Highways, Federal-aid Primary System 28 Highways and public roads, streets, highways, toll roads, freeways or 29 parkways in this State where the combination of vehicles as described 30 in this paragraph may lawfully operate. The commissioner shall 31 promulgate rules and regulations within 120 days after the effective 32 date of this amendatory act to identify a network of roads with 33 reasonable access for motor-drawn vehicles greater than 48 feet in 34 length but not more than 53 feet in length. The commissioner shall, in 35 establishing this network, consider all portions of the network for 48 36 foot long and 102 inch wide motor-drawn vehicles and specify those 37 routes or portions thereof where motor-drawn vehicles greater than 48 38 feet in length but not more than 53 feet in length shall be excluded 39 from lawful operation for reasons of safety. 40

(5) No combination of vehicles, including load or contents, consisting of more than two motor-drawn vehicles, as set forth in this subsection, and any other vehicle, shall be found or operated on any public road, street or highway or any public or quasi-public property in this State.

41 42

43

44

45 (6) The maximum overall length of a motor-drawn vehicle, as set 46 forth in this section, including load or contents or any part or portion

1 thereof, except as otherwise provided by this subsection, when 2 operated as part of a combination of vehicles consisting of two 3 motor-drawn vehicles and a drawing or power unit vehicle which is 4 not designed, built or otherwise capable of carrying cargo or loads, shall not exceed 28 feet for each motor-drawn vehicle in the 5 6 combination of vehicles. The provision of this paragraph shall not 7 apply to any vehicle or combination of vehicles designed, built and 8 utilized solely to transport other motor vehicles. The Commissioner of 9 Transportation, after consultation with the Director of the Division of 10 Motor Vehicles and the Superintendent of State Police, shall 11 promulgate rules and regulations specifying those portions or parts of 12 the National System of Interstate and Defense Highways, Federal-aid 13 Primary System Highways and public roads, streets, highways, toll 14 roads, freeways or parkways in this State where combinations of 15 vehicles as described in this paragraph may lawfully operate.

16 17

18

19

20

21

22

23

24

25

26

27

28

29

30

31

32

33

34

35 36

37

38

39

40

41

42

43

44

45

- (7) The maximum length and outside width of an omnibus found or operated in this State shall be established by rules and regulations promulgated by the Commissioner of Transportation, after consultation with the Director of the Division of Motor Vehicles and the Superintendent of State Police. Unless otherwise specified in the aforesaid rules and regulations, the maximum outside width shall be 102 inches; any other dimension established for width in the aforesaid rules and regulations shall be based upon a determination that operation of an omnibus with a width of less than 102 inches, but no less than 96 inches is required in the interest of public safety on those public roads, streets, highways, toll roads, freeways, parkways or the National System of Interstate and Defense Highways in this State specified in the aforesaid rules and regulations, or that operation of an omnibus with a width greater than 102 inches is not unsafe on those public roads, streets, highways, toll roads, freeways, parkways or the National System of Interstate and Defense Highways in this State specified in the aforesaid rules and regulations.
- (8) The maximum width and length of farm tractors and traction equipment and farm machinery and implements shall be established by rules and regulations promulgated by the Director of the Division of Motor Vehicles. The operation of the aforesaid vehicles shall be subject to the provisions of R.S.39:3-24 and they shall not be operated on any highway which is part of the National System of Interstate and Defense Highways or on any highway which has been designated a freeway or parkway as provided by law.
- (9) The maximum outside width of the cargo or load of a vehicle or combination of vehicles, including farm trucks, loaded with hay or straw shall not exceed 105 1/2 inches, but the maximum outside width of the vehicle or combination of vehicles, including farm trucks, shall otherwise comply with the provisions of paragraph (1) of this subsection. The Commissioner of Transportation, after consultation

- with the Director of the Division of Motor Vehicles and the Superintendent of State Police, may promulgate rules and regulations establishing a maximum outside width of 102 inches for the aforesaid cargo or load when operating on those highways where a greater
- width is prohibited by operation of law.

 (10) Notwithstanding the provisions of paragraphs (4) and (6) of
 this subsection pertaining to length, the Director of the Division of
- Motor Vehicles may adopt rules and regulations specifying maximum
 length dimensions for any vehicle or combination of vehicles designed,
- 10 built and utilized solely to transport other motor vehicles.

12

13

14

15

16

28

29

30

31

32

3334

35

36

3738

39

40

41

42

- (11) The provisions of this subsection pertaining to length shall not apply to a vehicle or combination of vehicles or special mobile equipment operated by a public utility, as defined in R.S.48:2-13, when that vehicle or combination of vehicles or special mobile equipment is used by the public utility in the construction, reconstruction, repair or maintenance of its property or facilities.
- (12) The provisions of this subsection pertaining to width shall not 17 18 apply to a recycling vehicle when that vehicle is used for the collection 19 of recyclable material on a street or highway other than a highway 20 which is designated part of the National System of Interstate and 21 Defense Highways in this State or as a freeway or parkway as 22 provided by law. The maximum outside width of any recycling vehicle 23 so used, including load or contents of any part or portion thereof, shall 24 be no more than 96 inches, except that the width may be up to 105 25 inches whenever that vehicle is operating at 15 miles per hour or less, 26 and access steps are deployed and recyclable materials are actually 27 being collected.
 - b. No vehicle or combination of vehicles, including load or contents, found or operated on any public road, street or highway or any public or quasi-public property in this State shall exceed the weight limitations set forth in this Title. Violations shall be enforced pursuant to subsection j. of section 5 of P.L.1950, c.142 (C.39:3-84.3).
 - Where enforcement of a weight limit provision of this Title requires a measurement of length between axle centers, the distance between axle centers shall be measured to the nearest whole foot or whole inch, whichever is applicable, and when the measurement includes a fractional part of a foot equaling six inches or more or a fractional part of an inch equaling one-half inch or more, the next larger whole foot or whole inch, whichever is applicable, shall be utilized. The term "tandem axle" as used in this act is defined as a combination of consecutive axles, consisting of only two axles, where the distance between axle centers is 40 inches or more but no more than 96 inches.
- In addition to the other requirements of this section and notwithstanding any other provision of this Title, no vehicle or combination of vehicles, including load or contents, shall be operated

in this State, unless by special permit authorized by this Title, with a gross weight, single or multiple axle weight, or gross weight of two or more consecutive axles, the allowance of which would disqualify the State of New Jersey or any department, agency or governmental subdivision thereof for the purpose of receiving federal highway funds.

(1) The gross weight imposed on the highway or other surface by the wheels of any one axle of a vehicle or combination of vehicles, including load or contents, shall not exceed 22,400 pounds.

For the purpose of this Title the combined gross weight imposed on the highway or other surface by all the wheels of any one axle of a vehicle or combination of vehicles, including load or contents, shall be deemed to mean the total gross weight of all wheels whose axle centers are spaced less than 40 inches apart.

- (2) The gross weight imposed on the highway or other surface by all the wheels of all consecutive axles of a vehicle or combination of vehicles, including load or contents, shall not exceed 34,000 pounds where the distance between consecutive axle centers is 40 inches or more, but no more than 96 inches apart.
- (3) The combined gross weight imposed on the highway or other surface by all the wheels of consecutive axles of a vehicle or combination of vehicles, including load or contents, shall not exceed 22,400 pounds for each single axle where the distance between consecutive axle centers is more than 96 inches; except that on any highway in this State which is part of, or designated as part of, the National Interstate System, as provided at 23 U.S.C.103(e), this single axle limitation shall not apply and in those instances the provisions of this Title as set forth at R.S.39:3-84b.(5) shall apply.
- (4) The maximum total gross weight imposed on the highway or other surface by a vehicle or combination of vehicles, including load or contents, shall not exceed 80,000 pounds.
- (5) On any highway in this State which is part of, or designated as part of, the National Interstate System, as provided at 23 U.S.C. 103(e), the total gross weight, in pounds, imposed on the highway or other surface by any group of two or more consecutive axles of a vehicle or combination of vehicles, including load or contents, shall not exceed that listed in the following Table of Maximum Gross Weights, for the respective distance, in feet, between the axle centers of the first and last axles of the group of two or more consecutive axles under consideration; except that in addition to the weights specified in that Table, two consecutive sets of tandem axles may carry a gross weight of 34,000 pounds each if the overall distance between the first and last axles of the consecutive sets of tandem axles is 36 feet or more. The gross weight of each set of tandem axles shall not exceed 34,000 pounds and the combined gross weight of the two consecutive sets of tandem axles shall not exceed 68,000 pounds.
 - In all cases the combined gross weight for a vehicle or combination

A1284 DECROCE, CHARLES

```
1
    of vehicles, including load or contents, or the maximum gross weight
 2
    for any axle or combination of axles of the vehicle or combination of
 3
    vehicles, including load or contents, shall not exceed that which is
 4
    permitted pursuant to this paragraph or R.S.39:3-84b.(2);
    R.S.39:3-84b.(3); or R.S.39:3-84b.(4) of this act, whichever is the
 5
 6
    lesser allowable gross weight.
 7
 8
    TABLE OF MAXIMUM GROSS WEIGHTS
 9
       Distance in feet
10
       between axle
11
       centers of first
12
       and last axles
13
       of any group
14
       of two or more
15
       consecutive axles
                                           7
                 3
                              5
                                     6
16
17
           axles axles axles axles axles
           22400 22400 22400 22400 22400 22400
18
    3
           34000 34000 34000 34000 34000 34000
19
    4
    5
           34000 34000 34000 34000 34000 34000
20
21
           34000 34000 34000 34000 34000 34000
    6
22
    7
           34000 34000 34000 34000 34000 34000
           34000 34000 34000 34000 34000 34000
23
    8
           39000 42500 42500 42500 42500 42500
24
    9
           40000 43500 43500 43500 43500 43500
25
    10
           41000 44000 44000 44000 44000 44000
26
    11
           42000 45000 50000 50000 50000 50000
27
    12
28
    13
           43000 45500 50500 50500 50500 50500
29
           44000 46500 51500 51500 51500 51500
    14
30
           44800 47000 52000 52000 52000 52000
    15
           44800 48000 52500 58000 58000 58000
31
    16
           44800 48500 53500 58500 58500 58500
32
    17
           44800 49500 54000 59000 59000 59000
33
    18
34
    19
           44800 50000 54500 60000 60000 60000
           44800 51000 55500 60500 66000 66000
35
    20
           44800 51500 56000 61000 66500 66500
36
    21
           44800 52500 56500 61500 67000 67000
37
    22
38
    23
           44800 53000 57500 62500 68000 68000
39
    24
           44800 54000 58000 63000 68500 74000
40
    25
           44800 54500 58500 63500 69000 74500
41
           44800 55500 59500 64000 69500 75000
    26
           44800 56000 60000 65000 70000 75500
42
    27
           44800 57000 60500 65500 71000 76500
43
    28
44
           44800 57500 61500 66000 71500 77000
    29
           44800 58500 62000 66500 72000 77500
45
    30
```

44800 59000 62500 67500 72500 78000

A1284 DECROCE, CHARLES

44800 60000 63500 68000 73000 78500

```
2
    33
           44800 60500 64000 68500 74000 79000
 3
    34
           44800 61500 64500 69000 74500 80000
 4
    35
           44800 62000 65500 70000 75000 80000
 5
           44800 63000 66000 70500 75500 80000
    36
           44800 63500 66500 71000 76000 80000
 6
    37
           44800 64500 67500 71500 77000 80000
 7
    38
 8
    39
           44800 65000 68000 72500 77500 80000
 9
    40
           44800 66000 68500 73000 78000 80000
10
    41
           44800 66500 69500 73500 78500 80000
    42
           44800 67200 70000 74000 79000 80000
11
           44800 67200 70500 75000 80000 80000
12
    43
           44800 67200 71500 75500 80000 80000
13
    44
    45
           44800 67200 72000 76000 80000 80000
14
15
    46
           44800 67200 72500 76500 80000 80000
           44800 67200 73500 77500 80000 80000
    47
16
           44800 67200 74000 78000 80000 80000
17
    48
           44800 67200 74500 78500 80000 80000
18
    49
           44800 67200 75500 79000 80000 80000
19
    50
           44800 67200 76000 80000 80000 80000
20
    51
21
    52
           44800 67200 76500 80000 80000 80000
22
    53
           44800 67200 77500 80000 80000 80000
           44800 67200 78000 80000 80000 80000
23
           44800 67200 78500 80000 80000 80000
24
    55
           44800 67200 79500 80000 80000 80000
25
    56
           44800 67200 80000 80000 80000 80000
26
    57
27
    58
           44800 67200 80000 80000 80000 80000
28
    59
           44800 67200 80000 80000 80000 80000
29
           44800 67200 80000 80000 80000 80000
    60
30
           44800 67200 80000 80000 80000 80000
    61
           44800 67200 80000 80000 80000 80000
31
    62
           44800 67200 80000 80000 80000 80000
32
    63
    64
           44800 67200 80000 80000 80000 80000
33
34
    65
           44800 67200 80000 80000 80000 80000
           44800 67200 80000 80000 80000 80000
35
    66
           44800 67200 80000 80000 80000 80000
36
    67
           44800 67200 80000 80000 80000 80000
37
    68
           44800 67200 80000 80000 80000 80000
38
    69
39
           44800 67200 80000 80000 80000 80000
40
       c. The dimensional and weight restrictions set forth herein shall not
41
    apply to a combination of vehicles which includes a disabled vehicle or
42
    a combination of vehicles being removed from a highway in this State,
```

provided that such oversize or overweight vehicle combination may

not travel on the public highways more than five miles from the point

where such disablement occurred. If the disablement occurred on a limited access highway, the distance to the nearest exit of such

A1284 DECROCE, CHARLES

1 highway shall be added to the five-mile limitation.

- d. The Director of the Division of Motor Vehicles may promulgate rules and regulations, including the establishment of fees, for the issuance, at his discretion and if good cause appears, of a special written permit authorizing the applicant:
- (1) To operate or move a vehicle or combination of vehicles or special mobile equipment, transporting one piece loads that cannot be dismembered, dismantled or divided in order to comply with the weight limitations set forth in this act. The special written permit issued by the director shall be in the possession of the driver or operator of the vehicle or combination of vehicles or special mobile equipment for which said permit was issued; and
- (2) To operate or move a vehicle or combination of vehicles or specialized mobile equipment, transporting a load or cargo that cannot be dismembered, dismantled or divided in order to comply with the dimensional limitations set forth in this act. The special written permit shall be in the possession of the driver or operator of the vehicle or combination of vehicles or special mobile equipment for which the permit was issued; and
- (3) Under emergency conditions, to operate or move a type of vehicle or combination of vehicles or special mobile equipment of a size or weight, including load or contents, which exceeds the maximum size or weight limitations specified in this act.

24 (cf: P.L.1995, c.397, s.3)

2. This act shall take effect immediately.

ASSEMBLY TRANSPORTATION COMMITTEE

STATEMENT TO

ASSEMBLY, No. 1284

STATE OF NEW JERSEY

DATED: MARCH 2, 1998

The Assembly Transportation Committee reports favorably Assembly Bill No. 1284.

This bill would remove the current requirement that the tractor wheelbase of a motor-drawn vehicle not exceed 20 feet between the center of the front axle and the center of the rear single axle or tandem axles. Approximately 80% of the vehicles being manufactured today exceed this requirement.

This bill was pre-filed for introduction in the 1998 session pending technical review. As reported, the bill includes the changes required by technical review which has been performed.

SENATE TRANSPORTATION COMMITTEE

STATEMENT TO

ASSEMBLY, No. 1284

STATE OF NEW JERSEY

DATED: JUNE 22, 1998

The Senate Transportation Committee reports favorably Assembly Bill No. 1284.

This bill would remove the current requirement that the tractor wheelbase of a motor-drawn vehicle not exceed 20 feet between the center of the front axle and the center of the rear single axle or tandem axles. Approximately 80% of the vehicles being manufactured today exceed this requirement.

PO BOX 004 TRENTON, NJ 08625

Office of the Governor NEWS RELEASE

CONTACT: Gene Herman 609-777-2600

RELEASE: February 26, 1999

Gov. Christie Whitman today signed the following pieces of legislation:

A-1284, sponsored by Assembly Members Alex DeCroce (R-Essex/Morris/Passaic) and Joseph Charles, Jr. (D-Hudson), eliminates the current requirement that the tractor wheelbase of motor drawn vehicles, such as trailers and semi-trailers not exceed 20 feet between the center of the front axle and the center of the rear single axle or tandem axles. The requirement was applicable only to motor-drawn vehicles which were 53 feet in length. The 20-foot requirement was eliminated because the industry standard exceeds the 20-foot requirement. Approximately 80 percent of the vehicles being manufactured today exceed this requirement. The industry standard is approximately 24 feet in length. The 20-foot restriction was enacted to ensure that 53- foot motor vehicles would be able to effectively negotiate turns. The industry now advises that the distance between the axles is not an important factor in that regard. Rather, it is the distance between the kingpin of the motor-drawn vehicle and the centerline of the rear axle which is more determinative of a vehicle's ability to turn effectively. This distance is currently regulated by statute and is not altered by this bill.

A-1343, sponsored by Assembly Member Carol J. Murphy (R-Essex/Morris/Passaic) and Senator Anthony R. Bucco (R-Morris), permits a county park commission to lease park lands or concessions for a period not to exceed ten years. Current law limits the duration of such leases to five years. The time of the leases will continue to be subject to the approval of the board of Chosen Freeholders of each county.